

In the Claims:

Claims 1-4 (allowed)

Claims 5-6 (allowed)

7. (amended) The friction clutch of claim 5, wherein the pressure plate has a third resistance to thermal conductivity, said first resistance to thermal conductivity being higher than at least the second and the third resistance.

8. (quadruply amended) A single disc friction clutch for a motor vehicle, said friction clutch comprising:

_____ a clutch housing;

_____ a clutch disc;

_____ said single clutch disc being configured to be mounted on a transmission input shaft having a longitudinal axis;

_____ said single clutch disc being configured to be axially movable along the longitudinal axis of a transmission input shaft;

_____ a pressure plate;

_____ at least one friction lining mounted on said clutch disc;

_____ said at least one friction lining being configured to be disposed between said pressure plate and a flywheel;

_____ said pressure plate being configured and disposed to engage and disengage said clutch disc with a flywheel;

said pressure plate being configured and disposed to be axially movable along the longitudinal axis of a transmission input shaft;

a membrane spring;

said membrane spring being disposed between said clutch housing and said pressure plate;

said membrane spring being configured and disposed to bias said pressure plate;

said pressure plate comprising a first portion and a second portion;

said first portion of said pressure plate being disposed to contact said clutch disc;

said second portion of said pressure plate being disposed away from said clutch disc and having a radial length;

a thermal insulating member being configured to minimize heat conduction from said pressure plate to said membrane spring;

said pressure plate having a protrusion extending axially in the direction of said membrane spring;

said insulating member being disposed at said protrusion between said membrane spring and said first portion of said pressure plate and forming an insulating layer in contact with and along said length of said second portion;

said second portion of said pressure plate forming part of said protrusion and being disposed between said insulating member and said membrane spring to contact said membrane spring;

said insulating member being rigid and comprising a metal and being a single, one-piece element extending circumferentially about said pressure plate;

said metal of said insulating member being configured to minimize heat conduction from said first portion of said pressure plate to said membrane spring to minimize distortion of said membrane spring from thermal conduction of heat from said pressure plate to said membrane spring.